



SmartShrinkRate Tester

The SmartShrink Rate Tester uses visual algorithms to automatically capture warp and weft data of textiles before and after textile shrinkage rates testing. It then automatically calculates the shrinkage rate and generates corresponding data, which is recorded in the software. The process involves scanning and identifying the QR code on the textile product, generating corresponding data in the software, and saving it. This greatly improves the efficiency of shrinkage rate testing in textile factories and reduces human testing errors, ensuring accurate and reliable test results.

SmartShrinkRate Tester



Wide range of applications

It is suitable for knitted/woven fabrics, non-woven, laminated fabrics and elastic woven fabrics.

- Fast and accurate calculation, easy to operate
 Self-developed visual detection algorithms and detection systems, with high detection speed and accuracy.
- High-definition industrial camera with a Sony IMX183 sensor, with about 20 million pixels and higher imaging quality.
- Require an external computer for operation, and the SmartShrink is equipped with a built-in scanning system, which can automatically identify sample number and QR codes.
- Equipped with automatic data saving function
 The sample number, sample image, test data and related data all can be automatically saved. Test data can be exported with one click.
- User friendly

High-brightness LED illumination power, with software dimming and no flicker, soft light that is safe for the eyes. The full-aluminum body of the SmartShrink, presents simple and elegant appearance, and this machine is popular by high integration and easy operation.



Power

100-245V 50/60Hz 3A



Weight

40 kg

गगग

Dimension

810*680*1130mm (DxWxH)

Specifications

Test mode automatic test

Sample test size 200*200mm, 250*250mm, 350*350mm,

450*450mm, 460*460mm, 500*500mm,

10*10in. 15*15in. 18*18in.

An additional computer is required (optional)

Operating system: Windows 10/11 Processor: Intel Core i3 or above Memory: 16GB DDR4 or above

Hard disk: 500GB SATA, solid state drive recommended Graphics card: discrete graphics card 1G or more memory

Expansion interface: USB3.0 or USB3.1

Standards

AATCC 35 AATCC150 AATCC 179 Method 1 GB/T8630

GB/T 8628 ISO 3759